



REF : SITS 2025/02

ACL-Screed Industrial Top Smooth

DESCRIPTION

ACL-Screed Industrial Top Smooth is a pumped industrial underlayment base and wearing screed applied as a self-levelling industrial grade flooring system. It is extremely durable and functions as a pourable floor patch for and base or wearing screed in both industrial and commercial applications. ACL-Screed Industrial Top Smooth can be applied by pump or by hand up to 50 mm's in thickness and be topped of if required with ACL Industrial flooring range of coatings and screeds.

ADVANTAGES

- Single application screed
- Fast installations
- Excellent adhesion
- Moisture tolerant
- Suitable for resin finishes

RECOMMENDED USES

- Engineering and manufacturing
- Warehousing
- Engineering workshops.
- Automotive & aviation areas.
- Factory units.

PRODUCT INFORMATION

System thickness (dry)	Solids content by weight	Pack sizes	Pack make up	Shelf life	Storage
Upto 50mm plus in thickness	100 %	25kg.	1 X Bag	12 Months (Base & Hardener)	Keep out of direct sunlight. Store in a dry place, not below 15°C

DRYING TIMES & COVERAGE RATES at 20°C

Coverage rate	Pot life	Application temperature	Light traffic	Full traffic	Full chemical cure
25 kg. unit will cover 2sq m at 7mm	20 Minutes from mixing	5°C - 25°C	4 Hours	36 Hours	Up to 5 Days

